


QUICK START GUIDE

DC and DCC Operation of Atlas Gold Series HO Scale C424/C425 Diesel Locomotives



equipped with ESU LokSound
Select Sound-Decoders



12 May 2014, Version 1.1
for ESU Firmware Version 4.10.9171

Quick Start for DC and DCC Operation of Atlas Gold Series HO-Scale Alco C424/C425 Locomotives Equipped with ESU LokSound Select Sound-Decoders

Congratulations on your purchase of an Atlas Master™ Gold Series HO-scale model of an Alco C424/C425 locomotive that is factory-equipped with an ESU LokSound Select sound-decoder. This sound-decoder provides the highest quality sound plus state-of-the art motor control. Your locomotive can run on either conventional DC (with basic features) or on NMRA Digital Command Control (with full features).

This document describes the features of the LokSound Select sound-decoder installed in the Atlas HO Gold Series Alco C424/C425 locomotive when the locomotive is operated on DC and on DCC power. Please note that a few updates to the software used in this locomotive have been made. As a result, certain DCC function buttons operate somewhat differently than they did in the first two Atlas HO Gold Series locomotives (RS-3 and S-2) that were equipped with LokSound Select sound-decoders. You can download from the Atlas website the current version of the Atlas *User Manual*^[1], which includes this locomotive. This *User Manual* explains in detail the differences in DCC function key operation between various ESU software versions, as well as giving a more complete description of both DC and DCC operation.

DC Operation of your Atlas HO-scale Gold Series C424/C425 Locomotive

Using a standard variable-voltage DC power pack, turn the DC throttle up slowly until you begin to hear locomotive sounds (around 5 volts). You will hear the diesel engine *Start-Up sound sequence*, which lasts about 25 seconds. The locomotive will **NOT** move before the *Start-Up* sequence has been completed. The headlight facing the direction in which the locomotive will move turns on in its *Dim* state. Once the start-up sequence has been completed, turn up the throttle voltage up (to about 7 volts) until the locomotive starts to move. Note that you must turn the throttle to a higher setting than you would to make a non-sound locomotive start to move. The locomotive starts moving slowly due to built-in inertia from the *BEMF* (Back EMF) motor control. The headlight in the direction of movement will turn from *Dim* to *Bright*; the headlight facing the opposite direction will be *Off*.

On a DC-powered layout, an Atlas HO-scale Gold Series Alco C424/C425 locomotive will *automatically* produce sounds that are appropriate for its current state of operation. For example, the *Startup* sound sequence plays before the locomotive begins to move, and *Brake Squeals* play as the locomotive grinds to a halt. However, it is not possible to trigger individual sounds (such as the *horn* or *bell*) manually with DC track power. If you wish to have manual control of sounds, Atlas suggests that you invest in a *Basic DCC System* which will allow you to control all available sounds and other special effects in your locomotive and yet be essentially as simple to operate as a DC power pack. *Basic DCC Systems* that are currently available include the:

- NCE DCC Twin,
- MRC Prodigy Explorer DCC,
- MRC TECH 6 Sound Controller 6.0 (usable in smaller scales, but primarily intended for O-scale and larger).

Moreover, one can change certain operational characteristics of the locomotive when operating on DC power, using the same DCC programming that is used to change these characteristics in DCC operation. See Reference [1] for details. However, a *Standard* (full-featured) *DCC System*, as opposed to a *Basic DCC System*, may be needed to make some or all of these changes.

DCC Operation of your Atlas HO-scale Gold Series C424/C425 Locomotive

- **Start-Up Behavior**

As shipped from the factory, this locomotive behaves as follows at start-up:

- Locomotive sounds will start up immediately after DCC power is applied to the track. You will first hear the sounds of a diesel locomotive starting up from a powered-down state, followed by normal idling sounds and (after the DCC throttle is advanced) running sounds.
- Even if you advance the DCC throttle, the locomotive will NOT move until **AFTER** the entire *Start-Up sound sequence* has played.

If the above behavior at startup is acceptable, there is nothing more that you need to do. If, however, you would like your locomotive to behave differently, see Example 3 in Appendix 4 of Reference [1] to change the behavior described in the first Dash item and Example 1 in Appendix 4 of this same reference to change the behavior described in the second Dash item

- **DCC Functions Available in Atlas HO-Scale Gold Series Alco C424/C425 Locomotives**

The ESU LokSound Select sound-decoder provides a number of different DCC functions that can be triggered by pressing the appropriate key (e.g., press the “5” key to trigger DCC Function #5) on your DCC controller. The following table lists the DCC functions available in the ESU LokSound Select sound-decoder installed in Atlas Gold Series HO-scale C424/C425 locomotives.

DCC Function Key Operation for Atlas HO-scale Gold Series C424/C425 Locomotives

Function Key	Locomotive Behavior when Press Function Key	Function Behavior (Latching or Non-latching)	Works Only with Engine Sounds On	Works Only When Moving
F0	Front and Rear Headlights are directional.	Latching	No	No
F1	Bell (1 st push on/2 nd push off)	Latching	No	No
F2	Horn blows until push F2 key again	Latching	No	No
Horn	Horn blows only while Horn key held down	Non-Latching		
F3	Two Coupler Clank sounds alternate	Non-Latching	No	No
F4	Diesel Fans (1 st push on/2 nd push off)	Latching	Yes	No
F5	Dynamic Brake Fan (1 st push on/2 nd push off) Only active when prime mover sound on	Latching	Yes	Yes
F6	Optional Ditch Lights (1 st push on/2 nd push off)	Latching	-	-
F7	Switching Mode (1 st push on/2 nd push off)	Latching	No	No
F8	Audio Mute and Start Up/Shut Down	Latching	No	No
F9	Manual Notching Up sounds (1 st push on/2 nd push off)	Latching	Yes	No
F10	Manual Notching Down sounds (1 st push on/2 nd push off)	Latching	Yes	No
F11	AUX3 Function Output (1 st push on/2 nd push off). Preset to MARS light	Latching	-	-

**DCC Function Key Operation for Atlas HO-scale
Gold Series C424/C425 Locomotives (continued)**

Function Key	Locomotive Behavior when Press Function Key	Function Behavior	Works Only with Engine Sounds On	Works Only When Moving
F12	Dim Headlight (1 st push dim/2 nd push bright)	Latching	No	Yes
F13	AUX4 Func Output (1 st push on/2 nd push off)	Latching	-	-
F14	Talking Defect Detector sounds	Detector sounds play each time F14 is pressed	No	No
F15	Cab Radio Communication sounds	Radio communication sounds play each time F15 is pressed	No	No
F16	Rail-joint Clank sounds (1st push on/2nd push off) Only active when prime mover sound on	Latching	Yes	Yes
F17	Brake Set/Release sounds with each push	Non-Latching	Yes	Yes
F18	Sanding Valve sounds (1 st push on/2 nd push off)	Latching	Yes	No
F19	Short Air Let-off sounds	Press F19 twice	No	No
F20	Air Compressor sounds (1 st push on/2 nd push off)	Latching	Yes	No
F21	Pop Valve sounds (1 st push on/2 nd push off)	Latching	No	No

Section 4.1 in Reference [1] explains the operation of DCC functions F1 to F21 in detail.

Default Headlight Operation in Atlas HO-scale Gold Series C424/C425 Locomotives

Since prototype Alco C424/C425s were road locomotives, their headlights would normally be turned on only in the direction that the locomotive was moving. Furthermore, the switch controlling the headlight of a prototype locomotive is normally set to its *dim* position when the locomotive is standing still. The following table illustrates how Atlas's model C424/C425 locomotive mimics this behavior.

Light	Forward	Stopped after Forward	Reverse	Stopped after Reverse
Front Headlight	Bright	Dim	Off	Off
Rear Headlight	Off	Off	Bright	Dim

When the locomotive is first powered up, you may need to press the *F0* (or *Headlight*) key on your DCC system one or two times to turn on the directional front or rear headlight.

- **DCC Programming Locations**

Most DCC systems allow you to program a Configuration Variable (CV), such as the DCC address of a locomotive, in either of two places:

- On a special section of track not connected in any way to your layout and called the Program Track. (In DCC terminology, programming locomotives on the program track is called *Service Mode Programming*.)
- Anywhere on the Main Line (regular track) of your layout. [In DCC terminology, programming a locomotive on the main line of your layout is called either *Programming on the Main (POM)* or *Operations Mode (Ops Mode)* programming.]
- In almost all cases, the ESU LokSound Select decoder installed in your Alco C424/C425 locomotive can be programmed on your program track **WITHOUT** a Program Track Booster connected between the program track output of your DCC system and your physical program track. However, if you do need a Program Track Booster, Atlas recommends the PTB-100 from SoundTraxx.

- **Programming a New DCC Address for Your Locomotive**

The decoder in every Atlas Gold Series locomotive comes from the factory set to use the short address “3.” However, in order to control (independently) several locomotives on the same track at the same time, it is necessary that each locomotive have a unique DCC address. A convenient choice for the DCC address is the road number printed on the side of the locomotive’s cab. Frequently, the number on the side of the cab is a 3- or 4-digit number, which is treated in DCC as a Long (or 4-digit) Address.

If your DCC system allows you to program 4-digit addresses on the main line (many DCC systems do), Atlas recommends that you take advantage of this capability by programming the address of your Gold Series locomotive on the main line using Operations Mode (Ops Mode) programming.

- **Air Horn Selection**

For the Alco C424/C425, the default horn is a Nathan K5H (i.e., CV48 = 64). If you wish to use a different air horn, you may choose from the 16 air horns that are listed in the following table. To select a horn, write into CV48 the value listed to the right of the name of that horn in this table.

Air Horn Name	CV48 Value
Nathan K5H	64
Nathan K3L	65
Nathan M5	66
Nathan P3	67
Nathan P5A	68
Leslie S2M	69
Leslie RS3L	70
Leslie S3L	71
Leslie S5T	72
Nathan M3	73
Leslie RS3K	74
Nathan K5H	75
Leslie RS3L	76
Nathan M3H	77
Nathan K5H	78
Leslie 3 Chime	79

- **Resetting your Lok-Sound Select Equipped Loco to Factory Default Values**

Resetting the firmware in the LokSound Select sound-decoder to its factory-built configuration can resolve many problems that sometimes occur with firmware-controlled electronics. In fact, we have found that at least 20 to 25 percent of the problems with Gold Series locomotives that we receive for repair at Atlas can be resolved simply by resetting the sound-decoder. Hence, the very first step you take to resolve a problem should be to reset the LokSound Select sound-decoder in your locomotive using the following procedure:

- Place the locomotive on your program track and write the value 8 into CV8.
- Cycle power to the decoder first off and then on again by:
 - o Tipping the locomotive to one side so that all the wheels on the opposite side are off the rail,
 - o Holding the locomotive in this tipped position for 5 to 10 seconds,
 - o Slowly lowering the locomotive back down until all wheels are once again on the program track rails.

The second dashed item listed above (power cycling) is **extremely** important; do **not** omit it.

REFERENCES

- [1]. *User Manual: DC and DCC Operation of Atlas Gold Series Diesel Locomotives equipped with ESU LokSound Select Sound-Decoders*, Version 1.20, 07 May 2014 (or later). Download from Atlas model website:

<http://www.atlasrr.com/>

Choose *Support*, *DCC Support*, and then double click on the listing for this document.

- [2]. *LokSound Select User Manual for Diesel and Steam Decoders*, Third Edition (or later), May 2012. You can download the ESU *LokSound Select User Manual* document from the ESU website:

<http://www.esu.eu/en/start/>

by first selecting *DOWNLOADS*. Then click on *Instruction Manuals*. Next, click on *Digital Decoders*. Finally, single-click on the *Download* icon in the box labeled *LokSound Select Users Manual*.

Appendix: Body-Removal Instructions for Atlas HO-Scale C424/C425 Locomotives

When reading these instructions, please refer to the exploded diagram and parts list that was packed with your Atlas HO C424/C425 locomotive.

Instructions for Removing the Plastic Body Shell from an Atlas HO-scale C424/C425 Locomotive

1. The first thing to do is remove the fuel tank so that you have a place on the locomotive onto which you can hold.
2. Remove the couplers by unscrewing them.
3. Remove the hand rails from the cab and from the cab steps; do **not** remove them from the side sill casting.
4. There are three sets of tabs on the bottom of the shell that attach to the frame; refer to the exploded diagram for the locations of these tabs.
5. Push inwards at the rear of the shell to release the rear-most tabs on the shell from the frame. The tabs **must** clear the frame before the body can be removed.
6. Now push inwards on the shell at the location of the center set of tabs to release these tabs from the frame.
7. Finally, there are two tabs at the front of the shell. Release them in the same way that you released the rear and center sets of tabs.
8. Once all tabs are clear of the frame, the body shell should come off of the die-cast mechanism, but the sill casting will stay on.
9. Remember to be careful not to break the hand rails.

ESU License Agreement

Software License Agreement

1. ESU LokSound, GmbH & Co. grants you, the owner, and the right to use the software that is included with your LokSound Select system only with the locomotive that you purchased.
2. Copyright: The software is owned by Electronic Solutions Ulm GmbH & Co. and is protected by German copyright laws and international treaty provisions. Therefore, neither you nor anyone else may copy the software.

Proprietary Rights and Obligations

The structure and organization of the Software/Firmware are the valuable properties of Electronic Solutions Ulm GmbH & Co. You will not make or have made, or permit to be made, any copies of the Hardware, Software/Firmware code, or any portions thereof. You are not to modify, adapt, translate, reverse engineer, de-compile, disassemble or create derivative works based on the Hardware or Software/Firmware. Trademarks shall be used in accordance with accepted trademark practice, including identification of trademark owner's name. The LokSound Select Hardware, Software, and Firmware are covered by various US and foreign patents and patents pending.

No Other Rights

Electronic Solutions Ulm, GmbH & Co. retains ownership of the LokSound Select Hardware design and operating Software/Firmware code. Except as stated above, this agreement does not grant you any rights to intellectual property rights to the LokSound Select Software, Firmware or Hardware. The use of any trademarks as herein authorized does not give you any rights of ownership in that trademark.

© 2014 All rights reserved. Information in this publication supersedes that in all previous published material. The contents and the product it describes are subject to change without notice. LokSound is a registered trademark of Electronic Solutions Ulm (ESU) GmbH & Co. MRC is a trademark of Model Rectifier Corporation. All other trademarks are the property of their respective holders. Atlas Model Railroad Co., Inc. makes no representations or warranties with respect to this publication. In no event shall ESU be liable for any damages, direct or incidental, arising out of or related to the use of this publication. Issued: 05/2014